



[HOME](#) [ABOUT US](#) [SERVICES](#) [PRODUCTS](#) [CONTACT US](#) [SITE TOOLS](#) [GUESTBOOK](#)
[CPU Coolers](#) > Cofan Part #: KEM-200


Mobile Processor (MOBILE INTEL® CELERON®)

[Features](#) [Compatibility](#) [Heat Sink](#) [Integrated Fan](#) [PDF Document](#) [Miscellaneous](#)
**Features**

- Provides an excellent cooling solution for all the Intel Mobile Celeron microprocessors
- The CPU temperature is well below the maximum operating temperature for each microprocessor which provides a failure free-environment for the life of the processor

**Compatibility**

Intel Mobile Celeron 266 MHz. -750 MHz. (PGA + BGA)

**Heat Sink**

Alloy	Extrusion 6063 T5 Aluminum
Pedestal Size (L x W)	2.126" x 1.66" x 0.892" (54mm x 42.17mm x 22.66mm)
Pedestal Flatness	3/1000 per linear inch
Mechanical Mounting	Spring Loaded Fastene

**Integrated Fan**

Cofan Model:	KEM-200-05 KEM-200-05-4 KEM-200-12 KEM-200-12-4										
Size (LxWxH):	40.0mm x 40.0mm x 10.0mm										
Air Flow:	5.41 CFM at 6000 RPM										
Air Pressure:	0.119 InH2O										
Acoustic Noise	30.4 dB										
	<table> <thead> <tr> <th>PART #</th> <th>INPUT POWER</th> </tr> </thead> <tbody> <tr> <td>KEM-200-05</td> <td>5VDC, max 0.22A</td> </tr> <tr> <td>KEM-200-05-4</td> <td>5VDC, max 0.22A</td> </tr> <tr> <td>KEM-200-12</td> <td>12 VDC, max 0.11A</td> </tr> <tr> <td>KEM-200-12-4</td> <td>12VDC, max 0.11A</td> </tr> </tbody> </table>	PART #	INPUT POWER	KEM-200-05	5VDC, max 0.22A	KEM-200-05-4	5VDC, max 0.22A	KEM-200-12	12 VDC, max 0.11A	KEM-200-12-4	12VDC, max 0.11A
PART #	INPUT POWER										
KEM-200-05	5VDC, max 0.22A										
KEM-200-05-4	5VDC, max 0.22A										
KEM-200-12	12 VDC, max 0.11A										
KEM-200-12-4	12VDC, max 0.11A										

Tachometer Sensor Output:	Open Collector, TTL Signal, 2 Pulses per revolution
---------------------------	---

MTBF:	70,000 hrs.
-------	-------------

PDF Document

 [Download Specification](#) ▲

Miscellaneous

Weight: 42 grams ▲

[Terms of Use](#)

Copyright © 1994-2008 Cofan USA, Inc. All Rights Reserved. 